




PMT-2658

185 nm to 1010 nm Photon Counting or Analog PMT

ELEMENTAL ANALYSIS
FLUORESCENCE
GRATINGS & DEM SPECTROMETERS
OPTICAL COMPONENTS
FORENSICS
PARTICLE CHARACTERIZATION
RAMAN
SPECTROSCOPIC ELLIPSOmetry
SPR IMAGING

A high sensitivity photomultiplier tube provides good spectral response in the UV to near infrared




If you need a high sensitivity single point detector to measure small signals in the UV to NIR spectral region, the PMT-1658 photomultiplier tube from HORIBA Scientific is an excellent choice. With high quantum efficiency and multiple options for ambient or cooled housings, responsivity extends from 185 nm to 1010 nm. This is one of a number of single point detectors available from HORIBA Scientific. Contact us for further information.

Used in conjunction with optically optimized housings, these PMTs integrate seamlessly with HORIBA's extensive selection of monochromators. In addition, the SpectrAcq2 acquisition module allows for software integration with LabSpec, SynerJY or LabVIEW. With all of the additional Optical Building Blocks available from HORIBA, a user can easily go from individual components to a complete spectroscopy solution.

Features and Benefits

- Wide spectral responsivity from 185 nm to 1010 nm
- Ultra high sensitivity
- High quantum efficiency
- Compact ambient and TE detector housing options



Accessories

Various accessories are available for powering the detectors, optically coupling detectors to HORIBA monochromators, and data acquisition.


- Ambient housing, 1911F/G
- High voltage power supply, PMT-HVPS
- Ambient housing with integrated high voltage, DPM-HV/G
- Air-cooled TE housing, OB-3001
- Water-cooled TE housing, 1914F/G
- SpectrAcq2 photon counting module, SAQ2-302DPM



Specifications

Part number	PMT-2658	
Spectral response	185 nm – 1010 nm	
Photocathode material	InGaAs (Cs)	
Window material	UV glass	
Effective area of PMT	3 mm x 12 mm	
Supply voltage	1500 V DC	
Cathode sensitivity	QE at 260 nm	14% typical
	Luminous	100 μ A/lm typical
	Radiant at 400 nm	40 mA/W typical
Anode sensitivity	Luminous	16 A/lm typical
	Radiant at 400 nm	6.4×10^3 A/W typical
Gain	1.6×10^5 typical	
Anode dark current	1 nA	

Mechanical Diagram



OPTICAL BUILDING BLOCKS



HORIBA
Scientific

info.sci@horiba.com www.horiba.com/opticalbuildingblocks

USA: +1 732 494 8660
UK: +44 (0)20 8204 8142
China: +86 (0)21 6289 6060

France: +33 (0)1 69 74 72 00
Italy: +39 2 5760 3050
Brazil: +55 (0)11 5545 1500

Germany: +49 (0)89 4623 17-0
Japan: +81 (0)3 6206 4721
Other: +1 732 494 8660